

Tools

for installing coaxial and optical systems



braun teleCom products have stood for competence and continuity for more than 35 years. Extensive experience and constantly growing know-how make the components and systems an integral part of many FTTX and HFC broadband networks.

While, in many areas, our activities focus on the development and production of our own products, we also serve as distributor for selected high-performance partners to achieve best possible customer satisfaction.

braun teleCom is a product brand of Netceed. We are a global leader in distribution, logistics, technical engineering, and product design supporting the tele-

communications and broadband industry. We supply and distribute a comprehensive range of passive and active equipment and tooling for network deployment, upgrades, and maintenance, supporting all technologies including FTTH, FTTx, HFC, Wi-Fi, 5G/mobile, and data center.

Netceed's comprehensive portfolio of 90,000+ products from nearly 1,500 industry-leading suppliers, along with their value-added supply chain solutions support carriers' seamless delivery of high-speed Internet, Video, Data, and Voice services to Residential, Business, and Mobile Users.



CONTENT

1. COAXIAL TECHNOLOGY

2. CABINETS AND ACCESSORIES FOR POWER SUPPLY

3. OPTICAL SYSTEMS

4. TOOLS

Tools for installing coaxial systems 3

Mechanical tools4

Broadband cable stripping tools9

Measuring device OneExpert CATV10

Tools for installing optical systems 13

Fiber cleavers14

Splicing devices15

Mechanical tools16

Cleaning accessories20

Mobile label printers 21

BMP5122

BMP6123

5. CLICK & GO

6. AUTHORIZED DISTRIBUTION

TOOLS FOR INSTALLING COAXIAL SYSTEMS

Do you have questions concerning our products or want to place an order?

We look forward to your call!
+49 511 757086

Do you already know, which products you need?
shop.brauntelecom.com

Mechanical tools








for coaxial systems



55240100
Mounting handle for
connector 5/8 MU-RG11-CX3 7,5


55240700
Mounting handle for F-connectors
GF-UE-ULTRAEASE

55240600
Mounting handle for
connectors 3,5/12M-RG11-CX3

Item	Description	Order No.
	CC security tool for CC security shield Specialty tool for installing or removing the CC security shield (Order No. 54440000)	55445000
	Locking termination tool LTT-75 for CC-LT-R75 Special locking tool for terminator CC-LT-R75	55281000
	F-connector crimp handle Work aid with F-thread and plastic handle for comfortable working, suitable for every F-connector	55240000
	Mounting handle for connectors 5/8 MU-RG11-CX3 7,5 Work aid with plastic handle for a comfortable mounting of the 5/8 MU-CX3 connector	55240100
	Mounting handle for connectors IEC14M-RG11-CX3 7,5 Work aid with plastic handle for a comfortable mounting of the IEC14M-CX3 connector	55240400
	Mounting handle for connectors 3,5/12M-RG11-CX3 Work aid with plastic handle for a comfortable mounting of the 3,5/12M-CX3 connector	55240600
	Mounting handle for F-connectors GF-UE-ULTRAEASE Work aid with plastic handle for a comfortable mounting of the F-compression connectors GF-UE-6 (5,1) and GF-UE 4,9	55240700

Subject to technical changes!

55511500
Mounting tool
RTF 716-3,8L



55470000
Torque wrench
TW 307-AH-B

55490000
Torque wrench
TW 407 AH

Item	Description	Order No.
	Torque wrench TW 307-AH-B Tool to tighten the nut of F-connectors complying with torque standard of 3,4 Nm, suitable for all F-connectors with nut-size HEX 11	55470000
	Torque wrench TW 407 AH Tool to tighten the nut of F-connectors complying with torque standard of 4,5 Nm, suitable for all F-connectors with nut-size HEX 11	55490000
	Torque wrench TW 409 Tool to tighten the nut of F-connectors complying with torque standard of 4,5 Nm, suitable for all F-connectors with nut-size HEX 14	55510000
	Mounting tool HT-2206F Mounting tool to fix the F-nuts of F-cripp and F-CX3 compression connectors with nut-size HEX 11 onto F-females	55515200
	Mounting tool RTF 716-3,8L Mounting tool to fix F-cripp and F-compression connectors	55511500
	Rubber tool for cable support Cable holder made of flexible rubber for strong hold of the coax cable during F-connector mounting, useable for cables with 3 – 12 mm diameter	55240500
	CRP 106C-.262" +.324" Crimp tool for F-60-Mini Tool for F-60-Mini 3,2 / 5,6 (= .262" connector) as well as for all F-59-ALM ... and F-56-ALM ... (= .324" connectors)	55210000



55415300
POCKET
Compression tool CX3



55415500
Compression tool
CX3 universal

Item	Description	Order No.	
	CRP 106J-.360"+.475" Crimp tool for EPA	Tool for 3,5/12M-56-UNIV..., IEC14M-56-UNIV... and F-56-EPA... (= .360" connectors) as well as for 3,5/12M -RG11-EPA..., IEC14M-RG11-EPA..., 5/8MU-RG11-EPA..., FM-RG11-ALM... and FM-COAX6-ALM... (= .475" connectors)	55215000
	CRP 106H-.324"+.360" Professional crimp tool	Tool for all F-59-ALM... and F-56-ALM... (= .324" connectors) as well as for 3,5/12M-56-UNIV..., IEC14M-56-UNIV... and F-56-EPA... (= .360" connectors)	55220000
	CRP 106F-.324"+.475" Professional crimp tool	Tool for all F-59-ALM... and F-56-ALM... (= .324" connectors) as well as for 3,5/12M-RG11-EPA..., IEC14M-RG11-EPA..., 5/8MU-RG11-EPA..., FM-RG11-ALM... and FM-COAX6-ALM... (= .475" connectors)	55230000
	CAT-EX 59/6 compression tool	Tool for PPC compression connectors EX-59, EX-6, CMP MC 30 and CMP MC 37	55400000
	CAT-AS-IEC/F-FX Compression tool	Tool for compression connectors F-59-CX3..., F-56-CX3..., FM-RG11-CX3..., IECF-56-CX3... and IECM-56-CX3...	55410100
	POCKET Compression tool CX3	Tool for Cabelcon CX3 compression connectors F-59-CX3..., F-56-CX3..., IECF-56-CX3, IECM-56-CX3... and GF-UE ULTRA	55415300
	Compression tool CX3 universal	Tool for the Cabelcon compression connectors F-, BNC- and IEC- in all dimensions (for coax cable types RG59/RG6/RG7/RG11)	55415500
	Compression tool CX3 multimedia	CX3 compression tool Multimedia for Fm-60, F-56, IECm-59+60, IECF-59+56 and BNCm-60	55415600

Subject to technical changes!



55294000
Rotary cable stripper
for Minicable



55295205
Cable shears
RG6/RG59/PRG11

	Item	Description	Order No.
	Compression tool RG11 universal	Compression tool RG11 Universal for RG11-CX3 7,5	55415700
	Rotary cable stripper for Minicable, RG 6, RG 58, RG 59	Allround cable stripper for stripping of cable types Ören HD-063, HD-083, HD-103, HD-113 and Belden H123xx, H121xx, H126xx and LCD 130A with stripping lengths of 6,5 mm for each the inner conductor and the braid (for crimp types ALM, UNIV, EPA and MINI)	55294000
	Cable stripper RG 11	Cable stripper for cable types Ören HD-163 and Belden PRG11xx with 2 adjustable blades	55295000
	Cable stripper for RG6/59 w/ HEX 11 spanner	Cable stripper for cable types RG 6/59 with spanner fits for HEX 11 F-connectors	55295003
	Cable stripper CSS-5127, RG59 & RG6	Cable stripper for RG59 and RG6 cable types with stripping lengths of 12 mm (outer conductor) and 7 mm (inner conductor), suitable for the 2 port multimedia outlets btv-MMD-5xx-y	55295007
	Replacement blades CSS-110	Replacement blades for the cable stripper CSS-5127 with stripping lengths of 12 mm (outer conductor) and 7 mm (inner conductor), suitable for the 2 port multimedia outlets btv-MMD-5xx-y	55295008
	Cable shears RG6/RG59/PRG11	Cable shears for coaxial cables with an outer diameter of max. 10,2 mm	55295205
	Cable shears JIC-750	Cable shears for coaxial cables with an outer diameter of max. 19,05 mm	55295204

Subject to technical changes!








55295201
Cable shears JIC-755



55299500
Dual stripping tool for
corrugated cables



55515500
RPT cable checker

Item	Description	Order No.
	Cable shears CXC-1 Cable shears for coaxial cables with an outer diameter of max. 25,4 mm	55295200
	Cable shears JIC-755 Cable shears for coaxial cables with an outer diameter of max. 25,4 mm	55295201
	Perfect stripping of jacket, outer- and inner conductor in one step with high accuracy according to the stripping directions for each connector size. Only for Cabelcon connectors!	
	Stripping tool for iKx	55295500
	Stripping tool for nKx	55296000
	Stripping tool for qKx	55297000
	Stripping tool for sKx	55297500
	Specially designed for connection cables of the in-ground tap-off type Kabelmetall Cellflex HFC 1/2" Cu2Y. Perfect stripping of jacket, outer and inner conductor in one step with high accuracy according to the stripping directions of the 3,5/12f-C418 connector.	55299500
	Perfect stripping of jacket, outer- and inner conductor in one step with high accuracy according to the stripping directions for each connector size. Only for Cabelcon connectors!	
	Stripping tool for COAX 4	55298000
	Stripping tool for COAX 3	55299000
	RPT cable checker For connection testing with optical and sound alert	55515500

Subject to technical changes!

Broadband cable stripping tools

for i-n-q-s Kx KES connector systems



55295800
iKx



55296500
nKx



55297300
qKx



55297700
sKx

- Universal tool for controlled and safe removal of the outer jacket, cutting the outer conductor as well as deburring the inner conductor
- Stripping dimensions, adjustable at iKx and nKx tools (coax-cable termination box 30 mm or 45 mm KES connectors)

- Available in a convenient field case, a bag (usable with belt) or as single units
- Simplified and error-reduced handling due to the preset stripping dimensions

Stripping tool set in a suitcase

Item	Order No.
Stripping tool set iKx, nK and qKx, without replacement blades	55297400
Stripping tool set iKx, nKx and qKx, with one of each type replacement blades	55297402
Stripping tool set iKx, nKx, qKx, and sKx, without replacement blades	55297800
Stripping tool set iKx, nKx, qKx, and sKx, with replacement blade for each type	55297801

Accessories and parts

Item	Order No.
Replacement blade for iKx, nKx, qKx or sKx oversheath	55299004
Replacement blade for iKx, nKx, qKx dielectric	55299005
Replacement blade for sKx dielectric	55299006
Blade box small for 10 blades, blades not included	55299008
Blade box large for 10 blades, blades not included	55299009
Bag for 3 stripping tools (fig. bottom left)	55297815
Case for 4 stripping tools (fig. bottom right)	55297817

Stripping tool as single unit

Item	Order No.
Stripping tool for iKx cables	55295800
Stripping tool for nKx cables	55296500
Stripping tool for qKx cables	55297300
Stripping tool for sKx cables	55297700



Measuring device OneExpert CATV



OneExpert CATV
Frontal view



OneExpert CATV
Side view

The Viavi One Expert CATV helps technicians to fix disruptions as quickly as possible. The user-friendly multi-touch user interface and the automatic OneCheck™ tests make it easy to perform complex measurements due to a clear dashboard display with expressive results. In addition, the future-proof modularity provides years of support in the installation of CATV and home networks. Below you can find a selection of the OneExpert's most important features:

- Broadband measurements in record time
- Simplifies and speeds up test execution
- Reduces subsequent work
- Enables toe operator to recognize mistakes at a glance
- Highest screening against LTE due to aluminium housing
- Measurement of the whole frequency range in less than 2 minutes while automatically detecting the channel plan
- Options for 32 x 8 DOCSIS® 3.0, DOCSIS® 3.1, WiFi, 1-Gigabit-Ethernet and TrueSpeed™
- RF/DOCSIS® module swappable on-site
- Ready for WiFi 2,4/5 GHz, Bluetooth, StrataSync™
- Simultaneous ingress and downstream tests
- Troubleshooting of QAM carriers/home networks
- WLAN inspection within 2,4 GHz and 5 GHz networks
- Testing of Gigabit DOCSIS® services
- Install PON(RFoG networks, checking fiber endfaces and determining the optical power level as well as the RF performance
- Optional IP video tests

OneCheck Expert

Expert mode enables the use of configured test point compensations and specific limit plans. The operator has the possibility to define own OneCheck tests. Downstream, as well as DOCSIS test can be configured here.

Smart Access Anywhere (SAA)

Smart Access Anywhere (SAA) allows remote access to the OneExpert CATV (ONX-630) without being on the same local network. Remote access is useful for remote coaching, troubleshooting and training.

Sweeping

Compatible with SDA 5500/5510/5000 as well as SCU 1800 sweeping systems of Viavi Solutions.

TDR (Time-Domain Reflectometer)

Simple network analysis and cable length tests via reflection measurement.

Template management

You now have the option to manage different templates on your device. This allows to quickly choose between different configurations.



OneExpert CATV
Accessories

Parameter	ONX 620			ONX 620 special models		ONX 630	
	Base	IPX	TSX	TSX VFKD	TSX UM	NTX	SWX
Optionen							
DOCSIS® 3.1		opt.		●	opt.		●
DOCSIS® 3.0 Bonding - 32x8		●		●	●		●
TrueSpeed (via GBE interface)		opt.		opt.	opt.		opt.
IP video		opt.		opt.	opt.		opt.
VoIP (ethernet)		opt.		opt.	opt.		●
VoIP MOS (requires the VoIP option)		opt.		opt.	opt.		opt.
Home TDR		opt.		opt.	opt.		opt.
HL Leakage		opt.		opt.	opt.		opt.
Field view		opt.		opt.	opt.		opt.
Field view with reverse path signal generator (RSG)		opt.		opt.	opt.		opt.
Smart Access Anywhere (SAA)		opt.		opt.	opt.		opt.
OneCheck							
OneCheck: Dashboard	●	●	●	●	●	●	●
OneCheck: Downstream full scan (level; MER; BER; C/N; echo; GD; ICR)	●	●	●	●	●	●	●
OneCheck: Incline	●	●	●	●	●	●	●
OneCheck: Downstream ingress under carrier	●	●	●	●	●	●	●
OneCheck: SmartScan/MER & BER diagrams (bar chart for all channels)	–	–	●	●	●	●	●
OneCheck DOCSIS: Scan (level; MER; BER; C/N; echo; GD; ICR)	●	●	●	●	●	●	●
OneCheck DOCSIS: Upstream scan TX level; modulation; ICR	●	●	●	●	●	●	●
OneCheck DOCSIS: Throughput & package quality	–	–	●	●	●	●	●
SessionExpert: SmartScan comparison of TAP, termination box and CPE	–	–	●	●	●	●	●
SessionExpert: Detailed DOCSIS® service test comparison	–	●	●	●	●	●	●
SessionExpert: Any other test	●	●	●	●	●	●	●
Channel inspection							
ChannelCheck: Level/MER/BER over time, OFDM MER variation	–	–	●	●	●	●	●
DQI over time	●	●	●	●	●	●	●
Channel performance diagram, downstream (ICFE)	–	–	●	●	●	●	●
SmartScan™	–	–	●	●	●	●	●
Downstream spectrum with ingress under carrier	–	–	●	●	●	●	●
ChannelCheck: Full scan (Level; MER; BER; C/N; Echo; GD; ICR)	●	●	●	●	●	●	●
ChannelCheck: Constellation/incline/system display	●	●	●	●	●	●	●
DOCSIS® inspection							
DOCSISCheck: Level/MER/BER with ES/SES over time	–	–	●	●	●	●	●
Channel performance diagram, downstream (ICFE)	–	–	●	●	●	●	●
DOCSISCheck: DOCSIS channel scan: TX level; modulation type; ICFR	–	–	●	●	●	●	●
Downstream spectrum with ingress under carrier	–	–	●	●	●	●	●
DOCSIS® channel frequency performance diagramm, upstream	–	–	●	●	●	●	●
Throughput/package quality/traceroute/ping	–	●	●	●	●	●	●
Modem function (pass through at RJ-45 GB ethernet port)	–	●	●	●	●	●	●
Any other DOCSIS® test (DQI + TX level over time; channel scan, downstream level, MER, BER, C/N, Echo, GD, ICR (ICFR), OFDM MER variation)	●	●	●	●	●	●	●
Further functions							
Ingress interference radiation scan	●	●	●	●	●	●	●
Spektrum (forward path)	●	●	●	●	●	●	●
Quick test	●	●	●	●	●	●	●
Ethernet (speed test; ping/traceroute; FTP/HTTP upload/download)	–	●	●	●	●	●	●
WiFi – 2,4 & 5 GHz: SSID overview: Diagramm and table; SSID level over time	●	●	●	●	●	●	●
Integration of the mobile app	●	●	●	●	●	●	●
Support of optical fiber microscopes P5000i & opt. level meters: MP-60, MP-80	●	●	●	●	●	●	●
Support of SmartID and SmartID Plus	●	●	●	●	●	●	●
Network incl. test point compensation (TPC)							
Ingress Expert	opt.	opt.	opt.	●	●	●	●
DOCSIS Expert	opt.	opt.	opt.	●	●	●	●
Channel Expert	opt.	opt.	opt.	●	●	●	●
Full Scan/QuickCheck Expert	opt.	opt.	opt.	●	●	●	●
OneCheck Expert	opt.	opt.	opt.	●	●	●	●
Return Signal Generator	opt.	opt.	opt.	opt.	opt.	●	●
RSG Loopback	opt.	opt.	opt.	opt.	opt.	●	●
Sweeping							
Sweeping without wobble point	–	–	–	–	–	●	●
Forward sweeping	–	–	–	–	–	opt.	●
Reverse sweeping	–	–	–	–	–	opt.	●
Reverse Alignment	–	–	–	–	–	opt.	●
Order No.							

on request



TOOLS FOR INSTALLING OPTICAL SYSTEMS

Do you have questions concerning our products or want to place an order?

We look forward to your call!
+49 511 757086

Do you already know, which products you need?
shop.brauntelecom.com

Fiber cleavers



Fiber Cleaver V8
Order No. on request



The Cleavers V7, V7+ and V8 are fully automatic cleaving tools for 250 µm, 900 µm, flat ribbon and 2 – 12 fiber ribbon cables. The fully automatic cleaving tools enable fast and precise breaking of the fibers. With the devices V7+ and V8, the fiber remains are automatically collected in a waste disposal. The V8 is characterized by the fact that the breaking process is carried out in just one step.

- Easy operation, including fiber waste disposal (V7+ & V8)
- Universal fiber holder
- Blade with 16 positions (up to 48.000 cleaves)
- Compact and robust
- Automatic resetting
- Cleaving process in a single step (V8)

Parameter	Fiber Cleaver V7	Fiber Cleaver V7+	Fiber Cleaver V8
Fiber type	single fiber/fiber ribbon	single fiber/fiber ribbon	single fiber/fiber ribbon
Length [mm]	8 – 20	8 – 20	8 – 20
Cleaving angle	< 0,5° (single)	< 0,5° (single)	< 0,5° (single)
Lifespan of the blade	48.000	48.000	48.000
Work steps	2	2	1
Reset function	blade setback	blade setback	blade setback
Fiber holder	universal	universal	universal
Applicable fibers	250 µm, 900 µm, 3 mm flat ribbon- and jumper		
Fiber waste disposal	no	yes	yes
Order No.	on request	on request	on request



Splicing devices



View 7
Order No. on request

Splicing devices with jacket-centering

The fully automatic, jacket-centering and compact splicers View 1 and View 3 with active V-groove, 5"/4,3" high-res double-tapping LCD touch display and GUI create large and clear fiber images. Additionally, 3 LEDs enable easy working, even in dark environments.

- Active V-groove jack-centering
- Highest zoom and resolution
- 5"/4,3" (View 1) colored touch display
- Lighting with 3 LEDs
- Removable SOC fiber holder
- Protection against water, shock and dust

3 axis splicing device with core-centering (DACAS)

The fully automatic, core-centering splicers View 5, View 6 and View 7 use their 5" high-res LCD touch display to create large and clear fiber images. The devices enable a SOC (Splice-on-Connector) splicing. Furthermore, the View 6s features splicing of DIAMOND Alberino Splice-On-Connectors. Due to short splicing and heating times, the devices offer the highest efficiency possible and are therefore applicable even in demanding environments.

- Highest zoom and resolution
- 5" colored touch display
- Lighting with 3 LEDs
- Short heating time
- Splicing of DIAMOND Alberino Splice-On-Connectors
- Protection against water, shock and dust

Parameter	View 7	View 6s	View 5	View 3	View 1
Dimensions [mm]	160 x 133 x 155	152 x 147 x 175	147 x 130 x 155	143 x 130 x 155	137 x 132 x 126
Weight with/-out battery [kg]	2,8/2,17	2,43/2,07	2,21/1,85	2,31/1,95	1,7/1,45
Fiber count	single	single	single	single	single
Applicable fibers	SM (ITU-T G.652 & G.657)/MM (ITU-T G.651)/DS (ITU-T G.653)/NZDS (ITU-T G.655)				
Compatible fibers [mm]	0,25 – 3,00/indoor cables (VFH-40)				
Cleaving length [mm]	Ø 0,125 – 1, L 8 – 16	Ø 0,125 – 1, L 5 – 16	Ø 0,125 – 1, L 8 – 16	Ø 0,125 – 1, L 8 – 16	Ø 0,125 – 1, L 8 – 16
Sheath diameter [µm]	80 – 150	80 – 150	80 – 150	80 – 150	80 – 150
Splicing programs	max. 128	max. 128	max. 128	max. 128	max. 128
Heating programs	max. 32	max. 32	max. 32	max. 32	max. 32
Typ. splice loss	SM: 0,02 dB/MM; 0,01 dB/ DS/NZDS: 0,04 dB/ G.657: 0,02 dB (ITU-T standard)			SM: 0,03 dB/MM; 0,02 dB/ DS/NZDS: 0,04 dB/ G.657: 0,03 dB (ITU-T standard)	
Return loss [dB]	> 60	> 60	> 60	> 60	> 60
Splicing time	7 s/SM: 8 s	7s/SM: 9 s	7s/SM: 9 s	7s/SM: 9 s	7s/SM: 9 s
Heat shrink splice length [mm]	20 – 60 mm	20 – 60 mm	20 – 60 mm	20 – 60 mm	20 – 60 mm
Heating time	FP-03 typ. 13 s	FP-03 typ. 13 s	FP-03 typ. 13 s	FP-03 typ. 30 s	typ. 13 s
Results memory	latest 2.000	latest 2.000	latest 2.000	latest 2.000	latest 2.000
Tensile test	1,96 – 2,25 N	1,96 – 2,25 N	1,96 – 2,25 N	1,96 – 2,25 N	1,96 – 2,25 N
Operating conditions	0 – 5000 m above sea level/0 – 95 % rel. humidity/-10 to +50 °C/wind 15 m/s				
Storage conditions	0 – 95 % rel. humidity/-40 to +80 °C				
Power supply	AC input 100 – 240 V/DC input 9 – 14 V				
Splicing amount/heating with battery	9800 mAh battery capacity/typ. 355 splice-heat-cycles	4200 mAh Batteriekapazität/typ. 170 splice-heat-cycles	4200 mAh Batteriekapazität/typ. 170 splice-heat-cycles	4200 mAh Batteriekapazität/typ. 170 splice-heat-cycles	3800 mAh Batteriekapazität/ typ. 140 splice-heat-cycles
Aut. calibration	Automatic arc calibration at change of air pressure or temperature				
Electrode life span	Up to 3.500 arcs (increase possibly via electrode grinding device)				
Connections	USB 2.0/Mini USB	USB 2.0/Mini USB	USB 2.0/Mini USB	USB 2.0/Mini USB	Micro HDMI
Order No.	on request	on request	on request	on request	on request

Mechanical tools

for optical systems



55680129
CSR-1575



55680125
JIC-125



Item	Description	Order No.
JIC-125	Fiber stripping tool 250 to 125 µm	55680125
JIC-375	3-way fiber stripping tool Sheath 1,6 – 3 mm Buffer 900 to 250 µm Coating 250 to 125 µm	55680127
CSR-1575	Tool for stripping the cable sheath and scratching fiber tubes	55680129
JIC-186	Kevlar shears	55680130
	Tool for cutting tubes	
JIC-1022	0,6 mm; 0,8 mm; 1,0 mm; 1,3 mm; 1,6 mm; 2,0 mm; 2,6 mm	55680132
JIC-1626	0,4 mm; 0,5 mm; 0,65 mm; 0,8 mm; 1,0 mm; 1,3 mm	55680134
JIC-2030	0,25 mm; 0,32 mm; 0,4 mm; 0,5 mm; 0,6 mm; 0,8 mm	55680136

Subject to technical changes!



55680138
CST-1900

55680146
VFL-25



Item	Description	Order No.
CST-1900	Cable sheath stripping tool (4,5 – 29 mm) cuts radially – in the longitudinal direction and spiraling	55680138
MS-6	Mid span access tool 1,2 – 1,5 mm; 1,5 – 1,8 mm; 1,8 – 2,1 mm; 2,1 – 2,5 mm; 2,5 – 2,9 mm; 2,9 – 3,3 mm	55680140
MS-26	Mid span access tool 2,9 – 3,6 mm; 3,6 – 4,4 mm; 4,4 – 5,2 mm; 5,2 – 6,0 mm; 6,0 – 6,8 mm	55680142
MS-326	Mid span access tool 5,0 – 5,6 mm; 6,0 – 6,6 mm; 7,2 – 7,8 mm; 7,8 – 8,4 mm; 9,4 – 10,0 mm	55680144
VFL-25	Laser visual fault locator	55680146
VFL-150	Laser visual fault locator kit, incl. LC adapter	55680148




55680150
FPM-50

Item	Description	Order No.
	<p>FPM-50 Fiber power meter, 8 wavelengths 850 nm, 930 nm, 1300 nm, 1310 nm, 1490 nm, 1550 nm, 1625 nm, 1650 nm Range: -50 tot +26 dB</p>	<p>55680150</p>
	<p>TK-120 Fiber optic toolkit JIC-375, JIC-186, CST-1900, CSR-1575, FOD-2000, MS-6, SD-61, FL-2000, JIC-2288, JIC-842, FW-5, H90</p>	<p>55680160</p>
	<p>TK-150 Fiber optic toolkit TK-120 plus VFL-150, FCC-250, FC-220</p>	<p>55680165</p>
	<p>TK-160 Fiber optic toolkit TK-120 plus VFL-150, FCC-250, FCC-125</p>	<p>55680170</p>
	<p>FL-2000 LED lamp with zoom lens</p>	<p>55680172</p>

Subject to technical changes!



55680174
JIC-842



55680178
JIC-63050



55680180
MDC-14



Item	Description	Order No.
JIC-842	Telekom tongs	55680174
JIC-2288	Side cutter	55680176
JIC-63050	Cable cutter	55680178
MDC-14	Tool for cutting micro tubes up to 14 mm	55680180
Speedpipe cutter	Brand: Gabocom	55680182
Spare blades	For speedpipe cutter, brand: Gabocom	55680183
H-90	Toolbox	55680185



Cleaning accessories



55680117
Connector cleaner FCC-300



55680107
TB-80875



55680113
FCC-125
(orange)

ITW cleaning cloths

- Fiber cleaning cloth made of 100 % dust free material for cleaning connectors and fibers
- Each cloth measures 10,2 x 10,2 cm
- 100 pcs in resealable box
- Product dimensions (W x H x D): 16 x 14,5 x 3 cm

Order No. **55680102**

Soaked cleaning cloths FSA50

- Cleaning cloths for splice preparation
- Soaked with special fiber cleaning fluid
- Each cloth measures 9 x 11 cm
- 50 pcs in resealable box
- Product dimensions (W x H x D): 7,5 x 12,5 x 3,5 cm

Order No. **55680201**

TB-80875 swab moistener

- Miller swab moistener PE
- Empty
- With metal flap

Order No. **55680107**

Sticklers™ fiber optic splice & connector cleaner

- Fast evaporating, no residue optical grade cleaning fluid for cleaning fiber
- Not regulated for transport by land, sea, or air
- Nonflammable, nontoxic
- Dissipates electrostatic charges
- ROHS and REACH compliant
- Minimum of 400 cleaning procedures per can

Order No. **55680104**

Fluid dispenser FD-220

The FD-220 fluid dispenser is designed to store and dispense cleaning fluids, such as isopropyl alcohol, to clean the end-faces of fiber optic cables. With a spill-proof lid, 220 ml capacity, and suction pump, this fluid dispenser is the most convenient way of carrying and dispensing cleaning fluid.

- Comes without fluid
- Twist-lock pump can be locked/unlocked with a simple twist
- Spill-proof lid holds fluid securely, preventing waste from spills and leaks
- Easy-to-use pump delivers a controllable amount of fluid with each press
- Dimensions (W x D x H): 62 x 62 x 117,6 mm

Order No. **55680220**

Quick-Click cleaner

The Jonard Quick-Click cleaner is designed for exceptional cleaning performance on the fiber optic connectors, the core of the fiber and the contact surface of the adapters or connectors of the fiber. The firmly attached dust cap provides optimal protection for the microfibers cloth as well as the adapter. This glass fiber cleaner has a patented 360° rotating cleaning concept for extra wide cleaning in just one step with different nozzles for each connector. In addition, this glass fiber cleaner contains a lint-free microfiber cloth and is made of electrostatically safe material.

Item	Min. cleaning processes	Suitable for connectors	Order No.
FCC-120 (white)	500	MPO	55680111
FCC-125 (orange)	800	LC	55680113
FCC-250 (blue)	800	FC, SC, ST	55680115

Connector cleaner FCC-300

The Jonard Tools FCC-300 is an fiber optic connector cleaner with a brand new, nonwoven, synthetic cleaning cloth with great durability and improved reliability. This is strong enough for aggressive cleaning of large-scale contaminants on the optical fiber. More than 500 cleaning procedures are possible. The matching connectors are FC, SC, ST, LC and MU.

Order No. **55680117**

Fiber scraps disposal can FDC-66

The fiber scraps disposal can allows safe disposal of cleaved fiber ends. The twist cover locks scraps in the disposal can for safe and easy disposal. With a plastic top and bottom, the disposal can has a 60 ml capacity with a paperboard body and lightweight design to accommodate any tool kit or splice/connector station.

Parameter	FDC-66
Capacity [ml]	60
Dimensions [mm]	47 x 47 x 66
Weight [g]	16,33
Order No.	55680066

MOBILE LABEL PRINTERS

Do you have questions concerning our products or want to place an order?

We look forward to your call!
+49 511 757086

Do you already know, which products you need?
shop.brauntelecom.com

BMP51

Mobile label printer with Bluetooth® interface



BMP51
Order No. on request

When you need clear, durable labels on the spot, you need the BMP™51 Label Maker. It offers crisp printing, easy formatting, convenient label sizes, and portability required for electrical and datacom installations, laboratory identification, facility and safety labelling.

- **Change Material in Seconds**
User-friendly, easy-to-insert cassettes include label material and ribbon
- **Automatic formatting of labels**
The cartridges make use of the Smart Cell technology that tells the printer how to format your label properly. Just insert a cassette, the printer does the rest.
- **Fast printing**
Prints at a speed of 25,4 mm/second - so you do not have to wait for your labels.

- **Long-lasting, integrated cutting device**
The printer has a self-cleaning cutting device that easily cuts any material and holds the label until you need it.
- **Power options to ensure mobility**
The device can be operated via the mains connection, AA batteries or the rechargeable Li-Ion battery. With one charge, you can print more than 3.000 labels.
- **Wireless use**
The integrated Bluetooth® technology enables wireless use.
- **Extensive software**
Thanks to the LabelMark™ software, the printer offers barcode symbols, time and date stamping, import of graphics, automatic data serialization and much more.

**A BMP51 will be configured for you individually.
Please contact us regarding an Order No.**



BMP61

Mobile label printer
with WiFi interface



BMP61
Order No. on request

Flexible and fast label printer

The BMP™61 Label Printer provides an efficient solution for quickly identifying your cables and other technical components. Heat shrinking sleeves, self-lams, wrap-around labels, optical fiber flags, tags and more than 600 other label materials provide the right solution for every application.

Rugged & reliable

- Drop-tested and equipped with moulded rubber bumpers
- Large material loading bay for fast label material swaps
- Smart-cell cartridge technology enables auto-calibration
- Large color touchscreen
- 33,8 mm/second print speed: Don't wait on the label you need
- Rechargeable NiMH-Battery for increased autonomy

High-performance materials, excellent print quality

- Handles die-cut, continuous and custom labels up to 50,8 mm – also in bulk format
- Intuitive typing thanks to the AZERTY/QWERTY/QWERTZ/CYRILLIC keyboards
- 300 dpi print quality

Data management versatility

- USB list feature: read spreadsheets directly from external USB-memory and integrate the data in your labels ready for printing
- Integrated WiFi interface – compatible with mobile apps: create or load label templates with your smartphone and send them to your printer
- USB 2.0 ports (Type A & B) to copy large lists of label designs
- Works with LabelMark™ labelling software and Brady mobile apps

A BMP61 will be configured for you individually.
Please contact us regarding an Order No.




Do you have questions concerning our products or want to place an order?

We look forward to your call!
+49 511 757086

Do you already know, which products you need?
shop.brauntelecom.com





braun teleCom GmbH
Merkurstr. 3 c
30419 Hanover
Germany

Phone +49 511 757086
Fax +40 511 753169
info.de.hannover@netceed.com
www.brauntelecom.com